




39 Souhegan Street - P.O. Box 269, Wilton, New Hampshire 03086
TEL (603) 654-2002 FAX (603) 654-2533
email: sales@shp-seals.com - website: www.shp-seals.com

ISO 9001 Certified

MULTI-USE PIN



D	D TOLERANCE	MATERIAL	PLATING CODE (1) (2) (3)
.012	±.0005	ASTM-F15 (KOVAR)	01
.015	±.0005	ASTM-F15 (KOVAR)	01
.018	±.001	ASTM-F15 (KOVAR)	01
.020	±.001	ASTM-F15 (KOVAR)	01
.025	±.0015	Steel	02
.030	±.0015	Steel	02
.040	±.0015	Steel	02

PART NUMBER

Example Part No: 020 X 350 ROE K-01

PIN DIAMETER

PIN LENGTH

END CONDITION

RBE - Round Both Ends

ROE - Round One End

SC - Straight Cut

PLATING

MATERIAL

K - Kovar

S - Steel

- (1) Standard plating for ASTM-F15 is 50 microinches minimum GOLD per MIL-DTL-45204, Type III, Grade A over 100-200 microinches NICKEL per SAE AMS-C-26074.
- (2) Standard plating for STEEL is 50 microinches minimum GOLD per MIL-DTL-45204, Type III, Grade A over 200-400 microinches NICKEL per SAE AMS-C-26074.
- (3) Other plating options are available. Please contact SHP.
- (4) Other materials available dependant on size. Please contact SHP.

All dimensions are inches